

HYCON HPP18E FLEX POWER PACK



PRODUCT FEATURES

HYCON HPP18E FLEX is equipped with a 13,2 kW (18 HP) motor, and the flow can be set to 20 - 30 - 40 - 46 lpm which make it the perfect power pack for professional and specialized companies within concrete cutting and coring.

On electric power packs of other brands, the oil flow adjusts by means of valves, and in this case, the oil often overheats from insufficient cooling.

HYDRAULIC POWER PACK HPP18E FLEX

Item no. HPP18E FLEX	2020411
Oil Flow, l.p.m	20, 30, 40, 46
Oil Flow EU, l.p.m	20, 30, 40
Working Pressure nominal, bar	120
Pressure relief valve, bar	160
Pump	14cc gear pump
Electrical Motor	13,2 kW, 3x400 V / 13.2 kW 3x480V
Protection class	IP 55
Guaranteed sound power level, LWA dB at 40 l.p.m.	98
Sound pressure level 1m, LPA dB at 40 l.p.m.	86
Dimensions (LxWxH), mm	805x625x704
Dry weight, kg	135

ELECTRIC

13,2 kW 25A (depending on flow setting) /
3x400V/480V 50 Hz/60Hz
Oil flow lpm 1x20-30-40-(46*)

*) Only for sale outside EU

The power pack is mounted with a pressure relief valve to avoid a too high pressure. Furthermore, the very efficient air-cooling protects the power pack from overheating. The frequency converter incorporates a phase inverter, which ensures correct motor rotation.

Contact us for more information: hycon@hycon.dk / +45 9647 5200

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS • CORE DRILLS • POST DRIVERS • PICK HAMMER • LIGHT & HEAVY DUTY BREAKERS
SUBMERSIBLE PUMPS • ROCK DRILLS • UNDERWATER EQUIPMENT • GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S
Juelstrupparken 11
DK-9530 Støvring

Tel +45 9647 5200
Fax +45 9647 5201
www.hycon.dk

DISTRIBUTOR: